

指示計選択表

項目	仕様	分類					プラグイン型	
		特長	オートゼロ1段設定	2点式電磁弁開閉用	インテリジェント計装用	ローコスト計装用		ローコスト型簡易計装用
		型式	D500-SB	U102-2C/2C/S	D701	D801		D901
最大表示	±1000		●					
	±4999	●				●		
	±10000	●						
	±19999			●	●			
感度調整範囲 (mV/V)	0.5~3.0	●	●	●			●	
	0.80~3.0				●	●		
	1.00~5.0							
非直線性 (%)	0.01			●				
	0.02	●					●	
	0.05		●					
	0.10				●	●		
ゼロ点の温度影響 (μV/°C RTI 以内)	0.50			●				
	1.00		●		●	●		
	2.00	●						
	2.50						●	
感度の温度影響 (%/°C)	0.0015			●				
	0.0030				●		●	
	0.0050					●		
	0.0100	●	●					
コンパレータ段数	1	●	●					
	2			○				
	4			○	○	●		
外部出力	0~±5V			○	○			
	0~±10V						●	
	1~5V			○	○			
	4~20mA			○	○		●	
	RS-232C			○	○			
	RS-485			○	○			
	警報ブザー	●	●					
制御機能	風袋引き機能	●		●	●	●		
	風袋引きリセット機能	●		●	●	●		
	投入-排出			●	●	●		
	電磁弁開閉出力		●					
演算機能	ゼロトラッキング			●				
	デジタルフィルター			●	●			
印加電圧	DC5V/30mA			●	●	●		
	DC5V/60mA						●	
	DC10V/60mA	●	●					
ロードセル切り替え点	1	●		●	●	●	●	
	2		●					
所要電源	DC9~16V				●			
	DC9~30V			●				
	DC18~30V				●	●		

	DC20~30V						●
	AC100V	●	●				●
使用温度範囲	-10~40°C	●	●	●	●	●	
	0~55°C						●
外形寸法	W	96	330	96	96	96	50
	H	96	110	48	48	48	45
	D	150	215	137	75	80	85
重量		800g	2kg	350g	250g	300g	300g

\* ● : 標準、○ : オプション

\* 外部出力○オプションはご相談ください。